

Amendments to the Claims:

Please amend Claims 1, 3 through 7, 11 through 13, 15, 16, and 48 through 52, and 55 through 57 and add Claims 59 and 60 to read, as follows. Note that all the claims currently pending in this application, including those not presently being amended, have been reproduced below for the Examiner's convenience.

CA 1. **(Currently Amended)** A developer supply container, detachably mountable to an image forming apparatus, for supplying a developer to the image forming apparatus, said developer supply container comprising:

a main body for accommodating a developer, said main body being provided with an opening for permitting discharge of the developer; and

a driving force receiving portion for receiving a driving force for feeding the developer in said main body toward said opening, the driving force being supplied from a driving force supplying portion provided in the image forming apparatus;

~~wherein said driving force receiving portion is engageable with the driving force supplying portion by relative movement toward each other, and, and~~

~~wherein~~ a surface fastener, is provided on said driving force receiving portion, for disengageable engagement with a surface fastener provided on said ~~the~~ driving force supplying portion by relative movement toward each other.

2. **(Canceled)**

C1
²3. (Currently Amended) A developer supply container according to Claim 1,
wherein each of ~~said the~~ surface fastener of the driving force supplying portion and said
surface fastener of said driving force receiving portion has a plurality and the surface
fastener of the driving force supplying portion ~~includes a plurality of elastically deformable~~
projections, which are engageable with each other formed thereon;

~~wherein said plurality of projections of said surface fastener of said driving force~~
~~receiving portion are engageable with the plurality of projections of the surface fastener of~~
~~the driving force supplying portion.~~

³4. (Currently Amended) A developer supply container according to Claim ²3,
wherein each projection of said plurality of projections of said surface fastener of said
driving force receiving portion and the plurality of projections of the surface fastener of the
driving force supplying portion is thicker at a free end than at a base end thereof.

⁴5. (Currently Amended) A developer supply container according to Claim ²3,
wherein one of said plurality of projections of said surface fastener of said driving force
receiving portion and the plurality of the projections of the surface fastener of the driving
force supplying portion are configured in the form of loops and the other of said plurality
of projections of said surface fastener of said driving force receiving portion and the
plurality of projections of the surface fastener of the driving force applying portion are
configured in the form of hooks.

5/6. (Currently Amended) A developer supply container according to Claim 3,

wherein each projection of said plurality of projections of said surface fastener of said driving force receiving portion and the plurality of projections of the surface fastener of the driving force supplying portion is configured in the form of a frustum of a pyramid.

6/7. (Currently Amended) A developer supply container according to Claim 3,

wherein a free end of each projection of said plurality of projections of said surface fastener of said driving force receiving portion and the plurality of projections of the surface fastener of the driving force supplying portion is rounded.

Claims 8 through 10. (Canceled)

7/11. (Currently Amended) A developer supply container according to Claim 1, further comprising a collecting portion for receiving dropouts from ~~wherein said driving force receiving member includes a projection formed on said surface fastener of said driving force receiving portion member, which projects toward the driving force supplying member, so as to surround a projection formed on the surface fastener of the driving force supplying portion.~~

8/12. (Currently Amended) A developer supply container according to Claim 11, further comprising a weir for collected dropouts at an end portion of said collecting portion ~~wherein a free end of said projection of said surface fastener of said driving force receiving member is bent.~~

9
13. (Currently Amended) A developer supply container according to Claim 7 or
8/12, wherein said collecting portion surrounds said a free end of the projection of the
surface fastener of said the driving force receiving portion at a circumference thereof
supplying member is folded back.

14. (Canceled)

10
15. (Currently Amended) A developer supply container according to Claim 1,
further comprising:
a sealing member for unsealably sealing said opening; and
a feeding member for feeding the developer in said main body toward said opening,
wherein said feeding member is integrally rotatable with said sealing member by
the driving force received by said driving force receiving portion.

11
16. (Currently Amended) A developer supply container according to Claim 1,
wherein said surface fastener of said driving force receiving portion is disposed at a leading
end side of said developer supply container in a mounting direction thereof relative to the
image forming apparatus provided at one end of said main body adjacent to said opening;
and said main body is rotatable by the driving force received by said driving force
receiving portion.

H. N. 60
12/17/03
17
Claims 14 through 47. (Canceled)

¹²
~~48~~. (Currently Amended) A developer supply container according to Claim 1,
wherein said main body has ~~is of~~ a cylindrical shape.

¹³
~~49~~. (Currently Amended) An image forming unit detachably mountable to an
image forming apparatus, said image forming unit comprising:
an image bearing member; and
a driving force receiving portion for receiving a driving force for rotating said
image bearing member, the driving force being supplied from a driving force supplying
portion provided in the image forming apparatus; and
a surface fastener, provided on said driving force receiving portion, for
disengageable engagement with a surface fastener provided on the driving force supplying
portion by relative movement toward each other
wherein ~~said driving force receiving portion is engageable with the driving force~~
~~supplying portion by relative movement toward each other, and~~
wherein ~~a surface fastener is provided on said driving force receiving portion for~~
~~disengageable engagement with a surface fastener provided on the driving force supplying~~
~~portion.~~

¹⁴
~~50~~. (Currently Amended) An image forming unit according to Claim ¹³~~49~~, wherein
each of said the surface fastener of the said driving force receiving portion and the surface
fastener of the driving force supplying portion and said surface fastener of said driving
force receiving portion have a plurality includes a plurality of elastically deformable
projections, which are engageable with each other formed thereon, and

C1
Cont

wherein said plurality of projections of said surface fastener of said driving force receiving portion are engageable with the plurality of projections of the surface fastener of the driving force supplying portion.

¹⁵
~~51~~. (Currently Amended) An image forming unit according to Claim ¹⁴~~50~~, wherein each projection of the said plurality of projections of the said surface fastener of the said driving force supplying receiving portion and said the plurality of projection of said the surface fastener of the driving force receiving applying portion is thicker at a free end than at a base end thereof.

¹⁴
~~52~~. (Currently Amended) An image forming unit according to Claim ¹⁴~~50~~, wherein one of said plurality of projections of said surface fastener of said driving force receiving portion and the plurality of projections of the surface fastener of the driving force supplying portion are configured in the form of loops and the other of said plurality of projections of said surface fastener of said driving force receiving portion and the plurality of projections of the surface fastener of the driving force supplying portion are configured in the form of hooks.

¹⁷
~~53~~. (Previously Added) An image forming unit according to Claim ¹⁴~~50~~, wherein each projection of said plurality of projections of said surface fastener of said driving force receiving portion and the plurality of projections of the surface fastener of the driving force supplying portion is configured in the form of frustrum of a pyramid.

18
54. (Previously Added) An image forming unit according to Claim ~~50~~¹⁴, wherein a free end of each projection of said plurality of projections of said surface fastener of said driving force receiving portion and the plurality of projections of the surface fastener of the driving force supplying portion is rounded.

19
55. (Currently Amended) An image forming unit according to Claim ~~49~~¹³, further comprising a weir for collected dropouts at an end portion of said collecting portion wherein said driving force receiving member includes a projection formed on said surface fastener of said driving force receiving member, which projects toward the driving force supplying member, so as to surround a projection formed on the surface fastener of the driving force supplying portion.

20
56. (Currently Amended) An image forming unit according to Claim ~~55~~¹⁹, further comprising a weir for collected dropouts at an end portion of said collecting portion wherein a free end of said projection is bent.

21
57. (Currently Amended) An image forming unit according to Claim ~~55~~¹⁹, wherein said collecting portion surrounds said surface fastener of said driving force receiving portion at a circumference thereof a free end of said projection is folded back.

22
58. (Previously Added) An image forming unit according to Claim ~~49~~¹³, further comprising as a unit at least one of developing means for developing a latent image on said image bearing member, charging means for electrically charging a surface of said image

bearing member, and cleaning means for cleaning the surface of said image bearing member.

C1
Cont

²³
--59. (New) A developer supply container according to Claim ¹¹~~16~~, wherein a mounting direction of said developer supply container relative to the image forming apparatus is a longitudinal direction of said developer supply container.

²⁴
60. (New) A developer supply container according to Claim ¹⁰~~15~~, wherein said opening is capable of being opened automatically using a connecting force between said surface fastener of said driving force receiving portion and the surface fastener of the driving force supply portion.--
